

## Hydraulic Landing Gear

Ideal solutions for 5th Wheeler, Gooseneck and Large Semi-Trailers.



**AJ 1/24**  
3,600kgs



**AM 1/24**  
5,400kgs



**AM 2/24**  
10,800kgs



**SL 2/24**  
15,000kgs

Specification	AJ	AM				SL-24
Capacity (Per Jack)	3,600kgs	5,400kgs				7,900kgs
Dimension	8.9 x 8.9cm	10.1 x 10.1cm				-
Cylinder Bore	2" (5cm)	2.5" (6.3cm)				3"(7.6cm)
Stroke Length	24" (60.9cm)	16" (40.6cm)	20" (50.8cm)	24" (60.9cm)	30" (76.2cm)	24" (60.9cm)
Retracted Length	89.8cm	69.2cm	79.3cm	89.8cm	104.8cm	74.3cm
Extended Length	150.8cm	107.5cm	127.8cm	148.1cm	178.6cm	135.2cm
Weight	34 kgs	30kgs	34kgs	38.5kgs	44kgs	25.5kgs

# Hydraulic Tube in Tube Jack



**CT**

7,700kgs



**SM**

11,300kgs



**HM**

25,800kgs



**OM**

18,100kgs

**OMX**

22,600kgs

Specification	CT	SM				HM	OM
Capacity (Per Jack)	7,700kgs	11,300kgs				15,800kgs	18,100kgs
Dimension	11.4 x 11.4cm	12.7 x 12.7cm				14 x 14cm	16.7 x 16.7cm
Cylinder Bore	3" (7.6cm)	3.5" (8.9cm)				4" (10.1cm)	4.5" (11.4cm)
Stroke Length	20" (50.8cm)	16" (40.6cm)	20" (50.8cm)	24" (60.9cm)	30" (76.2cm)	20" (50.8cm)	16" (40.6cm)
Retracted Length	84.1cm	69.5cm	79.8cm	89.8cm	105.1cm	82.5cm	83.2cm
Extended Length	134.9cm	108.5cm	128.9cm	149.2cm	179.7cm	133.3cm	123.8cm
Weight	49kgs	52.5kgs	46.5kgs	59kgs	61kgs	75.5kgs	77kgs

## Optional steel storage box

