



Hydraulic Tube in Tube Levelling Systems

Ideal solutions for Large Trailers & Relocatable Structures



- ✓ One touch, push button Auto-level operation
- ✓ Audio and visual prompts notify user when levelling is in progress and complete
- ✓ Bluetooth capability to allow remote operation on your smart device

Benefits

- ✓ Includes Check Pilot valves
- ✓ Simple plug and play installation
- ✓ Built-in safety alarm
- ✓ 12/24V Options
- ✓ User-friendly design, ensuring effortless operation
- ✓ Prevents vehicle rocking and motion
- ✓ Massive load capacity
- ✓ Manual Override feature

Technical Information

Jack Options



CT

4,500kgs



SM

11,300kgs



HM

15,800kgs



OM

18,100kgs

OMX

22,600kgs

Specification	CT	SM				HM	OM
Capacity (Per Jack)	4,500kgs	11,300kgs				15,800kgs	18,100kgs
Dimension	11.5 x 11.5cm	14.2 x 14.2cm				14 x 14cm	16.7 x 16.7cm
Cylinder Bore	2.4" (6cm)	3.5" (8.9cm)				4" (10.1cm)	4.5" (11.4cm)
Stroke Length	24" (60.9cm)	16" (40.6cm)	20" (50.8cm)	24" (60.9cm)	30" (76.2cm)	20" (50.8cm)	16" (40.6cm)
Retracted Length	88.6cm	69.5cm	79.8cm	93.1cm	105.1cm	82.5cm	83.2cm
Extended Length	149.5cm	108.5cm	128.9cm	154cm	179.7cm	133.3cm	123.8cm
Weight	45kgs	52.5kgs	46.5kgs	59kgs	61kgs	75.5kgs	77kgs

REDFOOT
LEVELLING

Unit 1, 7 Abeles Street

Baringa QLD 4551

☎ (07) 5228 0211

✉ info@redfootlevelling.com

🌐 www.redfootlevelling.com

DEALER INFORMATION